

**Double
compressor
units
Max. 10 &
15 bar.**

Technical data T81803



Double compressor unit - max. 10 bar

Designation	Receiver volume	F.A.D. l/min.*	Displacement l/min.	R.P.M.	Motor		Dimensions in mm			Weight
					kW	HP	L	W	H	
KA3GD	280	224	314	1145	2X1,1	2X1,5	1540	500	1110	280
KA25BD	280	410	470	1220	2X1,5	2X2,0	1540	500	1060	300
KA11AD	500	1000	1276	610	2X4,0	2X5,5	1930	600	1230	455
KA112CD	500	1440	1600	765	2X5,5	2X7,5	2020	600	1310	572
KA112FD	500	1740	1914	925	2X7,5	2X10	2020	600	1310	572
KA112FD	1000	1740	1914	925	2X7,5	2X10	2020	863	1580	700

Double compressor unit - max. 15 bar

Designation	Receiver volume	F.A.D. l/min.*	Displacement l/min.	R.P.M.	Motor		Dimensions in mm			Weight
					kW	HP	L	W	H	
KA13CD	500	900	956	915	2X4,0	2X5,5	1930	600	1230	450
KA112AD	500	1260	1380	660	2X5,5	2X7,5	2020	600	1310	467
KA112BD	500	1592	1800	860	2X7,5	2X10	2020	600	1310	474
KA112BD	1000	1592	1800	860	2X7,5	2X10	2060	865	1550	690

* Free air delivery at 50 degrees C, absolute inlet pressure 1 bar and inlet temperature 20 degrees C. Working pressure of the compressor 80% of max. working pressure.



STENHØJ
lifting the level

Stenhøj A/S
Denmark

Tel: +45 76 82 13 30
Fax: +45 76 82 13 31
Mail: info@stenhoj.dk
Web: www.stenhoj.dk

No liability accepted for specifications which are subject to alteration