

Supplementary units  
Max. 10 &  
15 bar.

## Technical data T81804



### Supplementary units - max. 10 bar

Designation	F.A.D. l/min.*	Displacement l/min.	R.P.M.	Motor		Dimensions in mm			Weight
				kW	HP	L	W	H	
KC3F	90	122	890	0,75	1,00	750	410	610	62
KC3G	112	157	1145	1,10	1,50	750	410	610	62
KC25B	205	235	1220	1,50	2,00	750	410	560	76
KC66B	270	400	1040	2,00	3,00	770	410	560	72
KC66A	310	475	1235	3,00	4,00	770	410	560	80
KC11A	500	638	610	4,00	5,50	970	460	630	138
KC112C	720	800	765	5,50	7,50	1020	500	600	160
KC112F	870	957	925	7,50	10,00	1020	500	600	165

### Supplementary units - max. 15 bar

Designation	F.A.D. l/min.*	Displacement l/min.	R.P.M.	Motor		Dimensions in mm			Weight
				kW	HP	L	W	H	
KC25A	185	218	1130	1,5	2,0	750	410	560	76
KC13B	360	380	725	3,0	4,0	970	460	630	126
KC13C	450	478	925	4,0	5,5	970	460	630	134
KC112A	630	690	660	5,5	7,5	1020	500	680	160
KC112B	796	900	860	7,5	10,0	1020	500	680	165

\* Free air delivery at 50 degrees C, absolute inlet pressure 1 bar and inlet temperature 20 degrees C. Working pressure of the compressor 80% of max. pressure.



**STENHØJ**  
lifting the level

Stenhøj A/S  
Denmark

Tel: +45 76 82 13 30  
Fax: +45 76 82 13 31  
Mail: info@stenhoj.dk  
Web: www.stenhoj.dk

No liability accepted for  
specifications which are subject to  
alteration