



DN	A	a	B	L	H	C	$\varnothing K$	$\varnothing D$
40	262	150	209	209	206	128	110	150
50	262	150	209	209	200	128	125	165
65	262	150	209	209	193	128	145	180
80	346	181	264	250	249	151	160	200
100	346	181	264	250	236	151	180	220
125	347	206	299	300	257	184	210	250
150	437	275	375	333	311	198	240	285
200	531	343	466	410	370	231	295	340
250	660	448	578	465	460	258	350	395
300	837	497	675	530	592	296	400	445
350	979	614	875	610	651	333	460	505
400	1005	614	875	610	626	333	515	565

All measurements in mm.

Pos	Item	Material	
		Spec. 1	Spec. 2
1	Body	Hot dip galv.	Aisi 316L
2	Cover	Hot dip galv.	Aisi 316L
3	*Screen	Aisi 316L	Aisi 316L
4	Screen clip	Aisi 316L	Aisi 316L
5	Flange	Hot dip galv.	Aisi 316L

*Option: flame, bug or rat screen

Option: different flange connections available

Approved by major classification societies.

This drawing/specification is the property of JOHN GJERDE AS and must neither be used, reproduced or handed over to a third party without our permission.

Revision		Revision		Scale	Date	Sign.
				%	21.05.10	MGS
					S-20563-20	
					21.05.10	MGS
					21.05.10	MGS
Mar.Dir.	Class	Owner	Title			
			AERO 1.6			
			Tank vent check valve			
Appr.			Flanged type - PN10			
			Draw. no.			
			S-20563-20			

