



*Option: flame, bug or rat screen

Option: different flange connections available

Approved by major classification societies.

DN	øD	B	L	øK	H	Weight
125	250	237	265	210	805	38 Kg
150	285	302	335	240	820	62 Kg
175	315	330	375	270	830	73 Kg
200	340	432	435	395	835	95 Kg
250	395	482	585	350	890	125 Kg

All measurement in mm

Pos	Item	Material	
		Spec. 1	Spec. 2
1	Body	Hot dip galv.	Aisi 316L
2	Swing check valve flange	Hot dip galv.	Aisi 316L
3	Swing check valve	Aisi 316L	Aisi 316L
4	Downspout cover brakett	Hot dip galv.	Aisi 316L
5	Flange	Hot dip galv.	Aisi 316L
6	Cover	Hot dip galv.	Aisi 316L
7	Inspection hatch	Hot dip galv.	Aisi 316L

This drawing/specification is the property of JOHN GJERDE AS and must neither be used, reproduced or handed over to a third party without our permission.

Revision		Revision	
Mar.Dir.	Class	Owner	Appr.
Title		Scale	
DOUBLE CHECK VENT VALVE		%	
For venting of mud tanks		Drawn	09.02.10 MGS
Flanged type - PN10		File	S-20543-10
		Check	09.02.10 MGS
		Plot	09.02.10 MGS
		Date	
		Sign.	
		Draw. no.	
		S-20543-10	

