



Stationary compressor units. 10 bar

Designation	Receiver volume	F.A.D. l/min.*	Displacement l/min.	R.P.M.	Motor		Dimension in mm			Weight
					kW	HK	L	W	H	
KA4F**	50V	60	91	1330	0,55	0,75	480	450	870	58
KA3G**	50V	112	157	1145	1,10	1,5	480	450	1010	100
KA3G	90	112	157	1145	1,10	1,5	480	450	1230	115
KA3G	150	112	157	1145	1,10	1,5	1260	430	980	140
KA25B	150	205	235	1220	1,50	2,0	1260	430	930	150
KA25B	275V	205	235	1220	1,50	2,0	750	600	1670	200
KA25B	280	205	235	1220	1,50	2,0	1560	500	1060	240
KA66B	90	270	400	1040	2,20	3,0	1190	410	870	135
KA66B	150	270	400	1040	2,20	3,0	1260	430	930	150
KA66B	275V	270	400	1040	2,20	3,0	750	600	1670	200
KA66B	280	270	400	1040	2,20	3,0	1560	500	1060	240
KA66A	90	310	475	1235	3,00	4,0	1190	410	870	135
KA66A	150	310	475	1235	3,00	4,0	1260	430	930	150
KA66A	275V	310	475	1235	3,00	4,0	750	600	1670	200
KA66A	280	310	475	1235	3,00	4,0	1560	500	1060	240
KA11A	275V	500	638	610	4,00	5,5	950	600	1730	270
KA11A	280	500	638	610	4,00	5,5	1560	530	1120	240
KA11A	500	500	638	610	4,00	5,5	1890	600	1230	343
KA112C	500	720	800	765	5,50	7,5	1890	600	1310	387
KA112C	1000	720	800	765	5,50	7,5	1880	865	1550	415
KA112F	500	870	957	925	7,50	10,0	1890	600	1310	387
KA112F	1000	870	957	925	7,50	10,0	2020	863	1580	500

V=Vertical

* Free air delivery at 50 degrees C, absolute inlet pressure 1 bar and inlet temperature 20 degrees C. Working pressure of the compressor 80% of max. pressure.

** With food grade oil



STENHØJ
lifting the level

Stenhøj A/S
Denmark

Tel: +45 76 82 13 30
Fax: +45 76 82 13 31
Mail: info@stenhoj.dk
Web: www.stenhøj.dk

No liability accepted for specifications which are subject to alteration