

**Stationary
Compressor
units
Max. 15
bar.**

Technical data T81802



Stationary compressor units- max. 15 bar

Designation	Receiver volume	F.A.D. l/min.*	Displacement l/min.	R.P.M.	Motor		Dimensions in mm			Weight
					kW	HP	L	W	H	
KA25A	90	185	218	1130	1,5	2,0	1190	410	870	143
KA25A	150	185	218	1130	1,5	2,0	1260	430	930	140
KA25A	275V	185	218	1130	1,5	2,0	750	600	1670	200
KA25A	280	185	218	1130	1,5	2,0	1560	500	1060	240
KA13B	275V	360	380	725	3,0	4,0	950	600	1730	276
KA13B	280	360	380	725	3,0	4,0	1560	530	1120	250
KA13B	500	360	380	725	3,0	4,0	1850	600	1240	325
KA13C	275V	450	478	925	4,0	4,5	950	600	1730	276
KA13C	280	450	478	925	4,0	5,5	1560	530	1120	250
KA13C	500	450	478	925	4,0	5,5	1930	600	1230	348
KA112A	500	630	690	660	5,5	7,5	1890	600	1310	387
KA112B	500	796	900	860	7,5	10,0	1890	600	1310	387
KA112B	1000	796	900	860	7,5	10,0	2020	863	1580	500

V=Vertical

* Free air delivery at 50 degrees C, absolute inlet pressure 1 bar and inlet temperature 20 degrees C. Working pressure of the compressor 80% of max. pressure.



STENHØJ
lifting the level

Stenhøj A/S
Denmark

Tel: +45 76 82 13 30
Fax: +45 76 82 13 31
Mail: info@stenhoj.dk
Web: www.stenhøj.dk

No liability accepted for specifications which are subject to alteration