



(SECTIONAL VIEW)

Notes:

- CERTIFICATION:** A0 & H0 Lloyd's Register of Shipping, Certificate No. SAS F100053 / L.R. addendum ref: CSD/SAS/FIRE/RDS/2168, Blast over-pressure to 1.35 bar g, Lloyd's Register of Shipping Certificate No. LWT 401087/1. (Approvals are also held through other Certifying Authorities, details of which are available upon request).
- MOVEMENT:** Standard seal construction will accommodate +/-25mm in any plane.
- CLIPPING:** Each seal is supplied with fitting instructions, adhesive and stainless steel worm drive clips to suit pipe and sleeve diameters. For diameters of 350mm and above 'double clipping' is required. The clipping length or cuff (B) is 30mm for single clips and 70mm for double clips.
- GENERAL:** The bulkhead penetration featured here may also be applied to a deck penetration.

Drawing Title:

DOUBLE HOT FACE FIRETEX PIPE PENETRATION SEAL SYSTEM A0 & H0 BULKHEAD



MCL UNITEX LTD
 MCL House, Adams Close,
 Heanor Gate Industrial Park,
 Heanor, Derbyshire,
 DE75 7SW
 United Kingdom
 Tel: +44 (0)1773 761226
 Fax: +44 (0)1773 533478
 Web: www.mclunitex.com

B	16/11/10	Cuff sizes altered	M.A.T.	J.D.	N.R.T.
A	02/06/10	Certification number revised	M.A.T.	J.D.	N.R.T.
0	20/09/05	Drawing Created	J.D.	N.R.T.	L.C.K.
Rev	Date	Revision detail	Drn	Chkd	App'd
Drawing Number			PPS-0150		REV B